

This data sheet details Thrislington Gulf material specification, options and dimensions.























Cleanroom specification falls into two sections:

Section One: Deals with the formalities of tendering, preliminaries, contractual, statutory and product performance considerations.

Section Two: Deals with the physical properties and performance fields of the product.

Standard Options

Composite Panel Code	Solid	Glaze	Base	Panel connection	Corner connection	Door	Door overpanel	RAL colour	Hardware	Complete from following Codes
Solid panel	Code <input type="text"/> : (see below) Modular twin tray construction with welded assembly.									
Panel skin	1mm thick slip coated pre-galvanised steel to JIS G 3302 or equivalent									
Panel thickness	80mm.									
Panel core	Honeycomb core.									
Glaze panel	Code <input type="text"/> : Half glaze Code <input type="text"/> : Full glaze									
Riser panel	Code <input type="text"/> (see below)									
Panel bases	Code <input type="text"/> : Standard Code <input type="text"/> : Recessed									
Head detail	Code <input type="text"/> (see below)									
Panel connection	Code <input type="text"/> : M/F									
Corner connection	Code <input type="text"/> : Corner cover									
Electrical cutouts	Code <input type="text"/> (see below) Code <input type="text"/> (see below)									
Roof cutout detail	Code <input type="text"/> (see below)									
Door overpanel	Code <input type="text"/> : Solid									
Solid Panel finish	Code <input type="text"/> PR : Polyester powder coating RAL									
Door Leaf	Code <input type="text"/> (see below) Modular twin tray construction with lock formed / seam welded assembly. double door with or without astragal.									
Door Skin	1mm thick slip coated pre-galvanised steel to JIS G 3302 or equivalent									
Door Leaf Thickness	44mm.									
Door Core	Honeycomb core.									
Frame	Code <input type="text"/> (see below)									
Door frame	1.5mm thick slip coated pre-galvanised steel to JIS G 3302 or equivalent.									
Frame assembly	Welded.									
Door frame and door finish	Code <input type="text"/> PR : Polyester powder coating RAL									
Vision panel options	Code <input type="text"/> : (see below) Size <input type="text"/> : (see below)									
Hardware options	Code <input type="text"/> : (see below)									

Panel configuration				Electrical cutouts		Frame configurations																																			
																																									
FS	HG	FG	RP	SOLID(horizontal) WITH ELECTRICAL CUTOUTS EL1	SOLID(vertical) WITH ELECTRICAL CUTOUTS EL2	S3	D3																																		
Panel bases		Head detail		Roof cutout detail		Door leaf configurations																																			
																																									
SB	RB	CL	LB	R1	R2	F	HG	FG	VS																																
Panel connections		Corner connections		Door overpanel detail		Standard frame connection		Dimensional Range(all dimensions are in mm)																																	
				<table border="1"> <thead> <tr> <th>Door Configurations</th> <th>Sizes</th> <th>Vision panel Configurations</th> <th>Sizes</th> </tr> </thead> <tbody> <tr> <td>S3</td> <td>1000x2100</td> <td>HG</td> <td>630x600</td> </tr> <tr> <td>D3</td> <td>2000x2100</td> <td>FG</td> <td>630x1750</td> </tr> <tr> <td colspan="2">Hardware options</td> <td>VS</td> <td>420x880</td> </tr> <tr> <td>A</td> <td>Personal entrance</td> <td></td> <td></td> </tr> <tr> <td>B</td> <td>Store or service</td> <td></td> <td></td> </tr> <tr> <td>C</td> <td>Passage corridor</td> <td></td> <td></td> </tr> <tr> <td>D</td> <td>Airlock rooms</td> <td></td> <td></td> </tr> </tbody> </table>		Door Configurations	Sizes	Vision panel Configurations	Sizes	S3	1000x2100	HG	630x600	D3	2000x2100	FG	630x1750	Hardware options		VS	420x880	A	Personal entrance			B	Store or service			C	Passage corridor			D	Airlock rooms						
Door Configurations	Sizes	Vision panel Configurations	Sizes																																						
S3	1000x2100	HG	630x600																																						
D3	2000x2100	FG	630x1750																																						
Hardware options		VS	420x880																																						
A	Personal entrance																																								
B	Store or service																																								
C	Passage corridor																																								
D	Airlock rooms																																								
M/F	C1	OP2																																							